



storing address &amp; register &amp; (initialization OR startup)

Search

☒ OSAPA Pilot: Search Engine I (long site list)
 ☐ Web Search

Results 1 - 10 for storing address &amp; register &amp; (initialization OR startup). (0.20 seconds)

## Refine results for storing address & register & (initialization OR startup):

<a href="#">Distros: debian, redhat, suse and ubuntu.</a>	<a href="#">kernel.org: Linux kernel code repository.</a>	<a href="#">Me</a>
<a href="#">Linux Man Pages</a>	<a href="#">Silicon Graphics Documentation</a>	<a href="#">Lir</a>
<a href="#">BSD operating systems</a>	<a href="#">freshmeat: catalog of UNIX applications.</a>	<a href="#">Of</a>
<a href="#">Desktop Projects: GNOME, KDE, X, freedesktop.</a>	<a href="#">SourceForge: host website for OSS development projects.</a>	<a href="#">Er</a>



### [hw-disk-ide](#)

initialization. All parameters must be set for the selected simulated drive (N=0 ... The "data port" register lives at address 0 in the command-block-bus. ...

[sources.redhat.com/sid/component-docs/hw-disk-ide.html](#) - 13k - [Cached](#)

### [Kernel initialization](#)

First what is done is the register EFLAGS is set to a predefined value of ... out what CPU it is running on, storing the value found in a variable \_cpu . ...

[www.freebsd.org/doc/en/books/arch-handbook/boot-kernel.html](#) - 24k - [Cached](#)

### [Bus Address Spaces \(Writing Device Drivers\) - Sun Microsystems](#)

Configuration space is used primarily during device initialization. It determines the location and size of register sets and memory buffers located on the ...

[docs.sun.com/app/docs/doc/802-5900/6i9kj7oop?a=view](#) - 28k - [Cached](#)

### [Mozilla/Netscape Address Book "HotSync"](#)

Since Mork is in-memory database, reading the data and storing it in memory ... wrapper around it so that module registration is automatic during startup. ...

[www.mozilla.org/mailnews/arch/MozAB\\_Palm\\_HotSync.html](#) - 48k - [Cached](#)

### [JCS - Remote Auxiliary Cache Client / Server](#)

Registry used to register and provide the # IRemoteCacheService service. ... If we startup another remote server listening to port 1103, (ServerB) then we ...

[jakarta.apache.org/jcs/RemoteAuxCache.html](#) - 17k - [Cached](#)

### [Summary of changes from v2.6.4 to v2.6.5 ...](#)

fixed the wrong register initialization on ALC655/658. .... new USB device on port 2, assigned address 8 > Initializing USB Mass Storage driver. ...

[www.kernel.org/pub/linux/kernel/v2.6/ChangeLog-2.6.5](#) - 358k - [Cached](#)

### [Using the GNU Compiler Collection \(GCC\)](#)

Because always storing floating-point arguments on the stack is inefficient and rarely needed, .... Do not use register r13 to address small data however. ...

[visual-mingw.sourceforge.net/doc/gcc-3.2.3/PS-6000-and-PowerPC-Options.html](#) - 25k - [Cached](#)

### [2 Installation and Startup Problems \(Solstice Enterprise Manager ...](#)

During MIS initialization, the following kinds of errors occur:. Storing ping\_up condition failed! Adding ping\_up condition failed! ...

[docs.sun.com/app/docs/doc/802-5967/6i9mj4eed?a=view](#) - 25k - [Cached](#)

### [Compiling Java for Embedded Systems](#)

This is safe, because the Java verifier does not allow storing an integer ... This means the actual initialization needed at run is very little most of it ...

[www.redhat.com/support/wpapers/cygnus/cygnus\\_compiling/compiling.html](#) - 18k - [Cached](#)

### [Troubleshooting Installation and Startup Problems](#)

Storing ping\_up condition failed! Adding ping\_up condition failed! Possible Cause: These error messages occurred during MIS initialization. ...

[docs.sun.com/source/816-2001/TBL\\_\\_startprobs.html](https://docs.sun.com/source/816-2001/TBL__startprobs.html) - 39k - [Cached](#)

[1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [Next](#)

---

storing address & register & (initialization OR startup)

[Search within results](#) | [Search Tips](#) | [Try Google Experimental](#)

---

©2008 Google - [Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)